

## Technical data sheet

### Cable fittings and accessories

**Metal EMC (Electro Magnetic Compatibility), Quick Installation, Vibration Proof**



#### Identification

Type TOP-T EMC Metal M40×1.5  
Part No. [FMM40-CV](#)

#### Product version

Datasheet version 00

#### Use/Application/Properties

Properties

- Adapts to different size cable shields
- 360° vibration proof shield termination
- Integrated strain relief
- Wide sealing and clamping range
- Updated design for easy installation
- Easy insertion of the cable from either end of the fitting
- Low contact resistance due to large alloy copper contacts
- manufactured acc. to EN 62444

#### Technical data

|                                |                                          |
|--------------------------------|------------------------------------------|
| Clamping range D               | 22 mm – 32 mm                            |
| Clamping range D               | 0.866 inch – 1.26 inch                   |
| Temperature range              | -20 °C ... +100 °C<br>-4 °F ... +212 °F  |
| Intermittent temperature range | -40 °C ... +150 °C<br>-40 °F ... +302 °F |
| Degree of protection           | IP68<br>Type 4X UL50E                    |
| Thread form                    | metric                                   |
| Thread standard                | metric acc. to EN 60423                  |
| Thread G                       | M40×1.5                                  |
| SW 1                           | 50 mm                                    |
| SW 2                           | 50 mm                                    |
| TL                             | 9 mm                                     |
| H                              | 62.5 mm                                  |

#### USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA  
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223  
[www.lutze.com](http://www.lutze.com) • [info@lutze.com](mailto:info@lutze.com)

22.05.2023 • Subject to technical modification

Part No. [FMM40-CV](#) • Datasheet version: 00

page 1 of 2



SYSTEMATIC TECHNOLOGY

## Technical data sheet

### Cable fittings and accessories

#### Construction

|                 |                       |
|-----------------|-----------------------|
| Description     | LUTZE TOP-T EMC       |
| Material        | Brass nickel-plated   |
| Material seal   | CR chloroprene rubber |
| Material O-ring | NBR                   |
| Surface         | nickel-plated         |

#### Approvals/Standards

|           |       |
|-----------|-------|
| Approvals | cULus |
|-----------|-------|

#### Notes and Comments

|      |                          |
|------|--------------------------|
| Note | Locknuts sold separately |
|------|--------------------------|

#### Dimensions

