

Technical data sheet

Cable fittings and accessories

Metal EMC (Electro Magnetic Compatibility), Quick Installation, Vibration Proof



Identification

Type TOP-T EMC Metal NPT 1"
Part No. [FMNPT10-CV](#)

Product version

Datasheet version 00

Use/Application/Properties

Properties

- Adapts to different size cable shields
- 360° vibration proof shield termination
- Integrated strain relief
- Wide sealing and clamping range
- Updated design for easy installation
- Easy insertion of the cable from either end of the fitting
- Low contact resistance due to large alloy copper contacts
- manufactured acc. to EN 62444

Technical data

Clamping range D	16 mm – 25 mm
Clamping range D	0.63 inch – 0.984 inch
Temperature range	-20 °C ... +100 °C -4 °F ... +212 °F
Intermittent temperature range	-40 °C ... +150 °C -40 °F ... +302 °F
Degree of protection	IP68 Type 4X UL50E
Thread form	NPT
Thread standard	per ANSI ASME B1.21.1
Thread G	NPT 1"
SW 1	40 mm
SW 2	40 mm
TL	20 mm
H	54 mm

USA: LUTZE INC.

13330 South Ridge Drive • Charlotte, NC 28273, USA
Tel. +1 (704) 504-0222 • Fax +1 (704) 504-0223
www.lutze.com • info@lutze.com

22.05.2023 • Subject to technical modification
Part No. [FMNPT10-CV](#) • Datasheet version: 00

Technical data sheet

Cable fittings and accessories

Construction

Description	LUTZE TOP-T EMC
Material	Brass nickel-plated
Material seal	CR chloroprene rubber
Material O-ring	NBR
Surface	nickel-plated

Approvals/Standards

Approvals	cULus
-----------	-------

Notes and Comments

Note	Locknuts sold separately
------	--------------------------

Dimensions

