

Technical data sheet

Cable fittings and accessories

LUTZE TOP-T Fittings Metric Plastic metric



Identification

Type TOP-T Plastic M20×1,5
Part No. [FPM20G-R](#)

Product version

Datasheet version 00

Use/Application/Properties

Properties

- Integrated strain relief
- Wide sealing and clamping range
- Easy to install
- manufactured acc. to EN 62444

Technical data

Clamping range D 7 mm – 12 mm
Clamping range D 0.276 inch – 0.472 inch
Temperature range -20 °C ... +100 °C
-4 °F ... +212 °F
Intermittent temperature range -40 °C ... +150 °C
-40 °F ... +302 °F
Degree of protection IP68
Diameter D 27 mm
Thread form metric
Thread standard metric acc. to EN 60423
Thread G M20×1.5
TL 10 mm
TD 20 mm
H 31 mm

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk

Germany: Friedrich Lütze GmbH

Postfach 12 24 (PLZ 71366) • Bruckwiesenstraße 17-19 • D-71384 Weinstadt
Tel. +49 (0)7151 6053-0 • Fax +49 (0)7151 6053-277(-288)
www.luetze.de • info@luetze.de

18.04.2023 • Subject to technical modification

Part No. [FPM20G-R](#) • Datasheet version: 00

page 1 of 2



SYSTEMATIC TECHNOLOGY

Technical data sheet

Cable fittings and accessories

Construction

Material	PA 6
Material seal	CR chloroprene rubber
Color	silver grey similar to RAL 7001

General

PU (units)	50
------------	----

Certifications/Standards

Certifications	cULus
----------------	-------

Notes and Comments

Note	Locknuts sold separately
------	--------------------------

Dimensions

