

## Technical data sheet

### Cable fittings and accessories

---

#### LUTZE TOP-T Fittings PG Plastic PG



---

#### Identification

---

Type TOP-T Plastic PG21  
Part No. [FPPG21B](#)

---

#### Product version

---

Datasheet version 00

---

#### Use/Application/Properties

---

Properties

- Integrated strain relief
- Wide sealing and clamping range
- Easy to install
- manufactured acc. to EN 62444

---

#### Technical data

---

Clamping range D	13 mm – 18 mm
Clamping range D	0.512 inch – 0.709 inch
Temperature range	-20 °C ... +100 °C -4 °F ... +212 °F
Intermittent temperature range	-40 °C ... +150 °C -40 °F ... +302 °F
Degree of protection	IP68
Diameter D	33 mm
Thread form	PG
Thread standard	PG according DIN 40430
Thread G	PG 21
TL	11 mm
TD	28.3 mm
H	37 mm

---

#### United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park  
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU  
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2  
[www.lutze.com](http://www.lutze.com) • [sales.gb@lutze.co.uk](mailto:sales.gb@lutze.co.uk)

#### Germany: Friedrich Lütze GmbH

Postfach 12 24 (PLZ 71366) • Bruckwiesenstraße 17-19 • D-71384 Weinstadt  
Tel. +49 (0)7151 6053-0 • Fax +49 (0)7151 6053-277(-288)  
[www.luetze.de](http://www.luetze.de) • [info@luetze.de](mailto:info@luetze.de)

18.04.2023 • Subject to technical modification

Part No. [FPPG21B](#) • Datasheet version: 00

page 1 of 2



SYSTEMATIC TECHNOLOGY

## Technical data sheet

### Cable fittings and accessories

---

#### Construction

---

Material	PA 6
Material seal	CR chloroprene rubber
Color	schwarz ähnlich RAL 9005

---

#### General

---

PU (units)	20
------------	----

---

#### Certifications/Standards

---

Certifications	cULus
----------------	-------

---

#### Notes and Comments

---

Note	Locknuts sold separately
------	--------------------------

---

#### Dimensions

