


Technical data sheet

Cable fittings and accessories

LUTZE TOP-T Locknuts Plastic Plastic NPT, PG and metric



Identification

Type	TOP-T Locknuts Plastic PG7
Part No.	LPPG7B

Product version

Datasheet version	00
-------------------	----

Use/Application/Properties

Properties	• Hexagonal locknut for secure tightening of plastic fittings, accessories and cables • Easy to install
------------	---

Technical data

Temperature range	-20 °C ... +100 °C -4 °F ... +212 °F
Intermittent temperature range	-40 °C ... +150 °C -40 °F ... +302 °F
Outer Ø	21 mm
Thread form	PG
Thread G	PG 7
SW	19 mm
H	5 mm

Construction

Material	PA 6 GF 30
Color	schwarz ähnlich RAL 9005

United Kingdom: LÜTZE Ltd.

Unit 3, Sandy Hill Park
Sandy Way, Amington • GB-Tamworth, Staffs B77 4DU
Tel. +44 (0)1827 31333-0 • Fax +44 (0)1827 31333-2
www.lutze.com • sales.gb@lutze.co.uk

Germany: Friedrich Lütze GmbH

Postfach 12 24 (PLZ 71366) • Bruckwiesenstraße 17-19 • D-71384 Weinstadt
Tel. +49 (0)7151 6053-0 • Fax +49 (0)7151 6053-277(-288)
www.luetze.de • info@luetze.de

18.04.2023 • Subject to technical modification

Part No. [LPPG7B](#) • Datasheet version: 00

page 1 of 2



SYSTEMATIC TECHNOLOGY

Technical data sheet

Cable fittings and accessories

General

PU (units) 50

Notes and Comments

Note Flange is imprinted with locknut size for easy identification.

Dimensions

