



# DSN20 RECEPTACLE

63-14042-352

## SPECIFICATIONS

20 A

480 VAC

Type 4X & IP69

3 hp

|                                  |                                              |
|----------------------------------|----------------------------------------------|
| Rated Current (A)                | 20 A                                         |
| Rated Voltage (V)                | 480 VAC                                      |
| Horsepower Rating                | 3 hp                                         |
| Contact Configuration            | 2P+G                                         |
| Auxiliary Contacts               | NO AUX                                       |
| Ratings Information              | CURRENT INTERRUPTING                         |
| Environmental Rating             | Type 4X<br>IP 66/67<br>IP 69                 |
| Short Circuit Rating             | 100 kA - CLOSE & WITHSTAND                   |
| Impact Rating                    | IK09                                         |
| Material                         | POLY                                         |
| Product Color                    | BLUE                                         |
| Minimum Operating Temperature    | -40F<br>-40C                                 |
| Maximum Operating Temperature    | 140F<br>60C                                  |
| Wiring Capacity - Phase Contacts | 14 AWG – 12 AWG<br>SCREW TERMINAL            |
| Applicable Standards             | UL 1682<br>cCSAus<br>C22.2 No. 182.1-13      |
| Option(1)                        | STRAIGHT INSERTION                           |
| Accessory Size                   | 1                                            |
| Base Drawing Number              | <a href="#">63-14xxx.PDF</a>                 |
| Catalog                          | <a href="#">meltric-catalog-dsn20-en.pdf</a> |