

GSA

Electronic/Glass Fuses

MIDGET, PC MOUNT & MINIATURE FUSES

FEATURES/BENEFITS

- Ceramic body
- Time-delay
- 1/4" x 1-1/4"

APPROVALS/ STANDARDS

- 1/2A through 8A, 250VAC, UL Listed
- 10, 12, 15A, 250V UL Recognized
- 1/2A through 8A, 250VAC, CSA Certified
- 10, 12, 15A, 250V CSA Recognized



STANDARD FUSE AMPERE RATINGS

Catalog Number	Ampere Rating	Volts	I.R.
GSA1/2	1/2A	250V	1
GSA3/4	3/4A	250V	1
GSA1	1A	250V	1
GSA1-1/4	1-1/4A	250V	2
GSA1-6/10	1-6/10A	250V	2
GSA2	2A	250V	2
GSA2-1/2	2-1/2A	250V	2
GSA3	3A	250V	2
GSA4	4A	250V	3
GSA5	5A	250V	3
GSA6	6A	250V	3
GSA6-1/4	6-1/4A	250V	3
GSA7	7A	250V	3
GSA8	8A	250V	3
GSA10	10A	250V	4
GSA12	12A	250V	4
GSA15	15A	250V	4

1. 250VAC @ 35A I.R./125VAC @ 10kA I.R.
2. 250VAC @ 100A I.R./125VAC @ 10kA I.R.
3. 250VAC @ 200A I.R./125VAC @ 10kA I.R.
4. 250VAC @ 750A I.R./125VAC @ 10kA I.R.
5. 250VAC @ 400A I.R./125VAC @ 10kA I.R.
6. 125VAC @ 400A I.R.

© 2025 Mersen. All rights reserved. Mersen reserves the right to change, update, or correct, without notice, any information contained in this datasheet.