



Project / Job Name:

Location:

Fixture Type:

Notes:

**65-577R1** - LED Emergency Backlit Flat Panel; 1 ft. x 4 ft.; Wattage and CCT Selectable; 120-277 Volt; ColorQuick Technology; PowerQuick Technology; White Finish



#### GENERAL

|                           |                                            |
|---------------------------|--------------------------------------------|
| Company                   | NUVO                                       |
| EA Height                 | 13.39                                      |
| EA Width                  | 2.56                                       |
| EA Length                 | 49.02                                      |
| Bulb Included             | Integrated                                 |
| Material                  | Aluminum / Steel                           |
| Fixture Type              | Backlit Flat Panel                         |
| Status                    | Active                                     |
| Style                     | Utility                                    |
| Surge Protection          | Built-in surge protection - 2KV            |
| Total Harmonic Distortion | 9%                                         |
| Wire Color                | White / Black / Green                      |
| Wire Length               | 3.54                                       |
| CCT Selectable            | Yes                                        |
| Wattage Selectable        | Yes                                        |
| Finish Family             | White                                      |
| Additional Info           | Driver Specs - VDC38-48V;<br>430/620/810mA |
| Amps                      | 0.200-0.072/0.300-0.108/0.400-0.144A       |
| Has Camera                | No                                         |
| Integrated Features       | Integrated Battery Backup                  |
| IOT Enabled               | No                                         |
| Lens Finish               | Frost                                      |
| Lens Material             | Poly methyl methacrylate (PMMA)            |
| Photo Cell                | No Photocell                               |
| Power Factor              | 0.9                                        |
| SDS Class                 | LED_Fixture                                |
| Indoor Outdoor            | Indoor                                     |
| Product Technology        | LED                                        |
| Incandescent Equivalent   | 100W-150W                                  |

#### ELECTRICAL

|                     |                               |
|---------------------|-------------------------------|
| CCT (Kelvin Temp)   | 3500K/4000K/5000K             |
| Dimmable            | Yes-Dimmable                  |
| Hours Rated         | 50000                         |
| Beam Angle (degree) | 120                           |
| Color Temp          | Warm to Cool White            |
| CRI                 | 80+                           |
| Dimming Type        | 0-10V Dimming                 |
| Operating Frequency | 50/60Hz                       |
| Operating Temp      | +1.4F to +113F (-17C to +45C) |
| Lumens              | 2200L-4600L                   |
| Volts               | 120V-277V                     |
| Watts               | 20W/30W/40W                   |

#### PHYSICAL

|               |                |
|---------------|----------------|
| Lamp Base     | Integrated     |
| Finish        | WHITE          |
| ANSI Base     | Integrated     |
| Lamp Type     | Integrated LED |
| Fixture Shape | Rectangle      |

#### ADDITIONAL INFO

|          |         |
|----------|---------|
| Warranty | 5-Years |
|----------|---------|

#### FEATURES

|              |     |
|--------------|-----|
| Flicker Free | Yes |
|--------------|-----|

#### PACKAGING

|               |                |
|---------------|----------------|
| UPC           | 045923657191   |
| Case Cube     | 0.9724         |
| Case Height   | 13.39          |
| Case Length   | 49.02          |
| Case Quantity | 1              |
| Case UPC      | 10045923657198 |
| Case Weight   | 6.7            |
| Case Width    | 2.56           |
| EA Cube       | 0.9724         |
| EA Height     | 13.39          |
| EA Length     | 49.02          |
| EA Quantity   | 1              |
| EA Weight     | 6.7            |
| EA Width      | 2.56           |
| Pack Type     | Box            |
| Web Height    | 3.09           |
| Web Length    | 47.72          |
| Web Width     | 11.84          |

#### COMPLIANCE

|                   |                     |
|-------------------|---------------------|
| Air Tight         | No                  |
| CA Prop 65        | Lead                |
| DLC ID            | S-DQR28P; S-CFTMMN  |
| FCC Compliant     | Yes                 |
| IC Rated          | Yes                 |
| IP Rating         | IP20                |
| Location Rating   | Damp                |
| NSF Approved      | Yes                 |
| ROHS Compliant    | Yes                 |
| Safety Listing    | cETLus - Listed     |
| California Ban    | Lawful for sale     |
| UL Application    | LED Panel Luminaire |
| DLC Approved      | Yes                 |
| Title 20          | Yes                 |
| T24/JA8 Compliant | No                  |