



Project / Job Name:

Location:

Fixture Type:

Notes:

65-582R1 - LED Backlit Flat Panel; 2 ft. x 4 ft.;
Wattage and CCT Selectable; 120-347 Volt; ColorQuick
Technology; PowerQuick Technology; White Finish



GENERAL

Company	NUVO
EA Height	25.2
EA Width	2.56
EA Length	49.02
Bulb Included	Integrated
Material	Aluminum / Steel
Fixture Type	Backlit Flat Panel
Status	Active
Style	Utility
Surge Protection	Built-in surge protection - 2KV
Total Harmonic Distortion	<20%
Wire Color	White / Black / Green
Wire Length	3.54
CCT Selectable	Yes
Wattage Selectable	Yes
Finish Family	White
Additional Info	Driver Specs - VDC38-48V; 630/810/1030mA
Amps	0.300-0.086/0.400-0.115/0.500-0.144A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lens Material	Poly methyl methacrylate (PMMA)
Photo Cell	No Photocell
Power Factor	0.9
SDS Class	LED_Fixture
Indoor Outdoor	Indoor
Product Technology	LED
Incandescent Equivalent	150W-175W

ELECTRICAL

CCT (Kelvin Temp)	3500K/4000K/5000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	120
Color Temp	Warm to Cool White
CRI	80+
Dimming Type	0-10V Dimming
Operating Frequency	50/60Hz
Operating Temp	+1.4F to +113F (-17C to +45C)
Lumens	3300L-5750L
Volts	120V-347V
Watts	30W/40W/50W

PHYSICAL

Lamp Base	Integrated
Finish	WHITE
ANSI Base	Integrated
Lamp Type	Integrated LED
Fixture Shape	Rectangle

ADDITIONAL INFO

Warranty	5-Years
----------	---------

FEATURES

Flicker Free	Yes
--------------	-----

PACKAGING

UPC	045923657146
Case Cube	1.8301
Case Height	25.2
Case Length	49.02
Case Quantity	1
Case UPC	10045923657143
Case Weight	12.24
Case Width	2.56
EA Cube	1.8301
EA Height	25.2
EA Length	49.02
EA Quantity	1
EA Weight	12.24
EA Width	2.56
Pack Type	Box
Web Height	1.5
Web Length	47.72
Web Width	23.75

COMPLIANCE

Air Tight	No
CA Prop 65	Lead
DLC ID	S-64SF75; S-BDG3F6
FCC Compliant	Yes
IC Rated	Yes
IP Rating	IP20
Location Rating	Damp
NSF Approved	Yes
ROHS Compliant	Yes
Safety Listing	cETLus - Listed
California Ban	Lawful for sale
UL Application	LED Panel Luminaire
DLC Approved	Yes
Title 20	Exempt
T24/JA8 Compliant	No