

Cable and Flexible Cord Connectors

For Non-Metallic Sheathed Cable

Type C-11LS

Type 806 & Type 906

2-Screw Connector

For round cable-open throat type

Use:

- Type C-11LS - to secure Non-Metallic Sheathed Cable to boxes and enclosures.
- Type 806 and Type 906 Series - to secure Non-Metallic Sheathed Cable, Service Entrance Cable and Flexible Cords to boxes and enclosures.

Features:

- Available with insulated throats
- Furnished with locknuts.
- Male hub threads NPS.

Material/Finish:

Malleable Iron/Zinc Electroplated

Third Party Certification:




UL Listed: E-11856
 UL Listed for 806, 906Z, 908, 909
 for NM and SE Cables
 UL Listed: E-11858
 UL Listed for 806, 906Z for SE Cable
 C-11LS - UL Listed for NM Cable.




Certified File No. 11584 NM Cable

Applicable Third Party Standards:


UL Standard: 514B
 CSA Standard C22.2 No. 18
 Fed. Spec: W-F-406E
 NEMA: FB-1




Type C-11LS



Type 806 — Type 908



Type 909



Trade Size (inches)	Catalog Number	Insulated Throat Catalog Number	Clamp Opening			Dimensions in Inches		
			Min.	Max.	Width	A	B	C
1/2	*C-11LS	*C-11LST	.19	.63	--	9/16	7/16	1 3/8
3/4	806	806T	.37	.84	.84	1 1/16	7/16	1 13/16
1	906Z	906T	.42	1.05	1.05	1 1/16	9/16	2 1/16
1 1/4	907	907T	.75	1.34	1.34	1 3/16	9/16	2 7/16
1 1/2	908	908T	.91	1.45	1.55	7/8	5/8	2 3/4
2	909	909T	1.39	2.03	2.03	1 5/16	3/4	3 3/8

*Longer screw to accommodate extra flexible cables. Not CSA Certified.