



Pass and Seymour Manual Controller

Part No. 7833MD



Three pole, Three Phase AC Manual Motor Controller 30 amp, 600 watts., Suitable as Motor Disconnect - 10KA @ 600VAC, 30A max Class J fuse.

Features & Benefits

High Horsepower rating of 20HP

Constructed of glass-reinforced thermoplastic

Heavy-duty zinc-plated steel strap, two brass rivets secure strap to housing

For covering patents, see www.legrand.us/patents.

Gull-wing shaped brass terminal pressure clamps

UL508 and cULus Listing of individual device and assembled device within enclosure

External screw-pressure-plate back and side wire terminal screws unstaked for use with ring terminals

For compatible wall plate options, from our TradeMaster unbreakable plates to our radiant screwless plates to our metal wall plates, [click here](#).

Specifications

General Info

Product Line	Pass & Seymour	Color	Aluminum
Finish	Matte	UPC Number	785007267709
Country Of Origin	Mexico	Features	Enclosed
Switch Type	Toggle	Number of Switches	1
Application Sector	Commercial, Industrial	Wall Plate Included	No
Standard	CSA Listed, UL Listed	Warranty Type	1-Year Limited Warranty
Type	Manual Controller		

Dimensions

Product Width US	4.5 in	Product Depth US	1.8 in
------------------	--------	------------------	--------

Product Height US	5.75 in
-------------------	---------

Listing Agencies / 3rd Party Agencies

cULus Listed	Yes
--------------	-----

Technical Information

Load Rating	30 A @ 600 VAC	Operating Cycles	50000
-------------	----------------	------------------	-------

Connection Location	Back and Side	Terminal Accommodation	#14 AWG - #10 AWG
---------------------	---------------	------------------------	-------------------

Number of Gangs	1	Throw Type	Triple Throw
-----------------	---	------------	--------------

Amperage	30 A	Enclosure Type	NEMA 3R
----------	------	----------------	---------

Number of Poles	3-Way	Requires Neutral Wire	Yes
-----------------	-------	-----------------------	-----

Indoor/Outdoor	Both	Mounting Type	On-Wall
----------------	------	---------------	---------

Wire Connection Type	Screw Terminals	Voltage	600.0 V
----------------------	-----------------	---------	---------

Load Type	CFL, Fluorescent, Halogen, Incandescent, LED, Universal, Xenon	Environmental Conditions	UL94 V2
-----------	--	--------------------------	---------
