



**Flexible Conduits & Fittings**

**T&B Catalog Number:**

BVIRA-U150

**UPC Number:**

78620995017

**Status:**

Active

**Description:**

PMAFIX black female thread adapter with UNEF threads. Material - polyamide 6, thread size - 5/8 in. - 24, conduit size NW - 10.

**Application**

For use in machine, vehicle and traction building

**Characteristics**

- Very high impact resistance
- Suitable for the AMP connector series CPC
- Vibration proof connection to PMAFLEX conduits
- High conduit pull-out strength
- Very good chemical properties
- Free from halogens and cadmium
- Fits both conduit profiles - Fine (T) and coarse (G)

**General**

Material	Polyamide 6
Color	Black
Thread Type	UNEF
Compatible With	PMAFLEX, AMP Connector series CPC

**Dimension Information**

Fits to Conduit Size (NW)	10
Fits to Conduit Size (metric)	12
Fits to Conduit Size (inches)	5/16
Thread Length (mm)	8.0
Thread Size (UNEF)	5/8" - 24
Connector Size (AMP)	11

**Technical Information**

Temperature Range-Continuous (Celsius)	-40 degree C to +105 degree C
Temperature-Short-Term (Celsius)	+160 degree C
Technical Data Sheet	Available on Website
Chemical Resistance Chart	Available on Website

**Specifications**

3dmodel	Available on Website
---------	----------------------

**IP Ratings**

IP Rating	IP68 stat. / IP67 dyn. On conduit side
-----------	--

**Packaging**

T&B Inner Pack	50
Package in Units	700
T&B Sold in UOM	Each
T&B Weight Per UOM	0.01 lbs. Each

**Application Support**

PMA Reference Guide	Available on Website
Product Overview-PMAFIX Connectors	Available on Website
PMAFIX Connectors-Safety and Sealing Systems	Available on Website

## Certifications

RoHS Compliance Yes

## Certifications



### For further technical assistance, please contact us...

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)