



## Flexible Conduits & Fittings

### T&B Catalog Number:

BVNV-M257

### UPC Number:

78620995237

### Status:

Active

### Description:

PMAFIX straight black connector, material - polyamide 6, thread size M25 x 1.5, conduit size NW - 17.

### Application

For cable protection systems in a wide range of applications

### Characteristics

Extremely high impact resistance  
Vibration proof connection to PMAFLEX conduits  
Easy mounting  
High conduit pull-out strength  
Very good chemical properties  
Free from halogens and cadmium  
Fits both conduit profiles - Fine (T) and coarse (G)

### General

Material Polyamide 6  
Color Black  
Thread Type Metric  
Compatible With PMAFLEX, PMA Smart Line

### Dimension Information

Fits to Conduit Size (NW) 17  
Fits to Conduit Size (metric) 20  
Fits to Conduit Size (inches) 1/2  
Thread Size (Metric) M25 x 1.5

### Technical Information

Temperature Range-Continuous (Celsius) -40 degree C to +105 degree C  
Temperature-Short-Term (Celsius) +160 degree C  
Technical Data Sheet Available on Website  
Chemical Resistance Chart Available on Website

### Specifications

3dmodel Available on Website

### IP Ratings

IP Rating IP68 stat. / IP67 dyn.

### Packaging

T&B Inner Pack 50  
Package in Units 250  
T&B Sold in UOM Each  
T&B Weight Per UOM 0.03 lbs. Each

### Application Support

PMA Reference Guide Available on Website  
Product Overview-PMAFIX Connectors Available on Website  
PMAFIX Connectors-Safety and Sealing Systems Available on Website

### Certifications

RoHS Compliance

Yes

---

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
[www.tnb.com](http://www.tnb.com)

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email: [techsupport@tnb.com](mailto:techsupport@tnb.com)