



Flexible Conduits & Fittings

T&B Catalog Number:

BVWD-M253GT

UPC Number:

78620995338

Status:

Active

Description:

PMAFIX 90 degree black one-piece universal elbow with universal safety clip. Material - polyamide 6, thread size - M25 x 1.5, conduit size NW - 23.

Application

In a wide range of applications where it is important that the cable protection system offers a high grade of sealing and safety.

Characteristics

High pull-out strength values
Vibration proof connection to PMAFLEX conduits
Hand opening not possible
Easy mounting, simple conduit push-in installation
Can be re-opened with a screwdriver
Self-extinguishing, free of halogen and cadmium and are extremely shock resistant
Fits both conduit profiles - Fine (T) and coarse (G)

General

Material Polyamide 6
Color Black
Thread Type Metric
Compatible With PMAFLEX

Dimension Information

Fits to Conduit Size (NW) 23
Fits to Conduit Size (metric) 25
Fits to Conduit Size (inches) 3/4
Thread Size (Metric) M25 x 1.5

Technical Information

Temperature Range-Continuous (Celsius) -40 degree C to +105 degree C
Temperature-Short-Term (Celsius) +160 degree C
Technical Data Sheet Available on Website
Chemical Resistance Chart Available on Website

Specifications

3dmodel Available on Website

IP Ratings

IP Rating IP66 stat. / IP54 dyn.

Packaging

T&B Inner Pack 30
Package in Units 150
T&B Sold in UOM Each
T&B Weight Per UOM 0.06 lbs. Each

Application Support

PMA Reference Guide Available on Website
Product Overview-PMAFIX Connectors Available on Website
Available on Website

PMAFIX Connectors-Safety and Sealing
Systems

Certifications

RoHS Compliance	Yes
-----------------	-----

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com