



Flexible Conduits & Fittings

T&B Catalog Number:

BVWV-M253

UPC Number:

78620995387

Status:

Active

Description:

PMAFIX 90 degree black one-piece universal elbow , material - polyamide 6, conduit size NW - 23, thread size - M25 x 1.5.

Application

In a wide range of applications where it is important that the cable protection system offers a high grade of sealing and safety.

Characteristics

High pull-out strength values

Easy installation with the oval clip guarantees an excellent connection to PMAFLEX conduits.

IP rating of up to IP68 can be achieved with the corresponding seals, NVN3 + SVN4.

Self-extinguishing, free of halogen and cadmium and are extremely shock resistant

Fits both conduit profiles - Fine (T) and coarse (G)

General

Material	Polyamide 6
Color	Black
Thread Type	Metric
Compatible With	PMAFLEX

Dimension Information

Fits to Conduit Size (NW)	23
Fits to Conduit Size (metric)	25
Fits to Conduit Size (inches)	3/4
Thread Size (Metric)	M25 x 1.5

Technical Information

Temperature Range-Continuous (Celsius) -40 degree C to +105 degree C

Temperature-Short-Term (Celsius) +160 degree C

Technical Data Sheet Available on Website

Chemical Resistance Chart Available on Website

Specifications

3dmodel Available on Website

IP Ratings

IP Rating IP68 stat. / IP67 dyn.

Packaging

T&B Inner Pack	30
Package in Units	120
T&B Sold in UOM	Each
T&B Weight Per UOM	0.07 lbs. Each

Application Support

PMA Reference Guide Available on Website

Product Overview-PMAFIX Connectors Available on Website

Available on Website

PMAFIX Connectors-Safety and Sealing
Systems

Certifications

RoHS Compliance	Yes
-----------------	-----

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com