



Flexible Conduits & Fittings

T&B Catalog Number:

BVYD-292323GT

UPC Number:

78620995417

Status:

Active

Description:

PMAFIX black one-piece 'Y' connector with universal safety clip, material - polyamide 6. Fits to conduit size NW - 29, 23, 23 .

Application

In a wide range of applications where it is important that the cable protection system offers a high grade of sealing and safety.

Characteristics

Self-extinguishing, free of halogen and cadmium and are extremely shock resistant

Very high impact resistance

Vibration-proof connection to PMAFLEX conduits

Easy mounting, simple conduit push-in instructions

High conduit pull-out strength

Can be easily re-opened with a screwdriver

Very good chemical properties

Fits both conduit profiles - Fine (T) and coarse (G)

General

Material Polyamide 6

Color Black

Suitable for Use With PMAFLEX, PMA Smart Line

Dimension Information

Fits to Conduit Size (NW) 29

Fits to Conduit Size (metric) 32

Fits to Conduit Size (inches) 1

Output fits to conduit size NW 23

Output fits to conduit size - Metric 25

Technical Information

Temperature Range-Continuous (Celsius) -40 degree C to +105 degree C

Temperature-Short-Term (Celsius) +160 degree C

Technical Data Sheet Available on Website

Chemical Resistance Chart Available on Website

Specifications

3dmodel Available on Website

IP Ratings

IP Rating IP66 stat. / IP54 dyn.

Packaging

T&B Inner Pack 10

Package in Units 50

T&B Sold in UOM Each

T&B Weight Per UOM 0.18 lbs. Each

Application Support

PMA Reference Guide Available on Website

Product Overview-PMAFIX Connectors Available on Website

Available on Website

PMAFIX Connectors-Safety and Sealing
Systems

Certifications

RoHS Compliance	Yes
-----------------	-----

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email:techsupport@tnb.com