



Flexible Conduits & Fittings

T&B Catalog Number:

NVAV-M323-13

UPC Number:

78620996282

Status:

Active

Description:

PMAFIX 45 degree black elbow with metric threads. Elbow material - polyamide 6, thread material-nickel-plated brass. Thread size - M32 x 1.5, conduit size NW - 23, thread length - 13.

Application

For applications with high technical requirements

Characteristics

Very high impact resistance

High thread and system connection strengths

Vibration-proof connection to PMAFLEX conduits

Easy assembly

High conduit pull-out strength

Very good chemical properties

Free from halogens and cadmium

Fits both conduit profiles - Fine (T) and coarse (G)

General

Material Polyamide 6

Color Black

Thread Type Metric

Compatible With PMAFLEX, PMAFLEX Pro, PMA Smart Line

Dimension Information

Fits to Conduit Size (NW) 23

Fits to Conduit Size (metric) 25

Fits to Conduit Size (inches) 3/4

Thread Length (mm) 13.0

Thread Size (Metric) M32 x 1.5

Technical Information

Temperature Range-Continuous (Celsius) -40 degree C - +105 degree C

Temperature-Short-Term (Celsius) +160 degree C

Technical Data Sheet Available on Website

Chemical Resistance Chart Available on Website

Specifications

3dmodel Available on Website

IP Ratings

IP Rating IP68

Packaging

T&B Order Multiple 30

T&B Inner Pack 30

Package in Units 120

T&B Sold in UOM Each

T&B Weight Per UOM 0.14 lbs. Each

Application Support

PMA Reference Guide Available on Website

Product Overview-PMAFIX Connectors Available on Website

Available on Website

PMAFIX Connectors-Safety and Sealing
Systems

Certifications

RoHS Compliance	Yes
-----------------	-----

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com