



Representative



Representative

Catalog Number: NVEZ-M506V-14
Product ID: 7TAA292210R0020
UPC Number: 78620996346
EAN Number: 07630030258411
Status: Active

VEZ Connector with Strain Relief, Metric Metal Thread - Thread M50x1.5, Fits to NW 36 F.CK 25/30/35 F.CU 40, Color Black

North American Specifications (UNSPSC)

UNSPSC	39121311 Electrical fittings
IGCC	4441 Electrical fittings
Brand Name	PMA
Type	Connectors-Straight
Application	EMC Sensitive Applications in Railway
Size	NW36
Material	Polyamide 6 with Nickel Plated Brass Threads
Insulation Class	IP68
Color	Black
Connection	M50
Temperature Rating	-40 Degrees C to 105 Degrees C; Short Term 160 Degrees C

European Specifications (ETIM)

ETIM	EC001176 Screw connection for corrugated plastic hose
Nominal diameter	40mm
Degree of protection (IP)	IP68
Model	Straight
Revolving thread	N
Construction type	Internal thread
Type of connection	Snap connection
Thread type	Metric
Thread connection size	M50 x 1.5
Thread material	Brass
Thread length	14mm
Total length	106mm
Material	Polyamide
Material sealing	Other
Colour	Black
Approved in combination with protective conduit CSA	N
Approved in combination with protective conduit UR	N
Approved in combination with protective conduit DIN EN 61386-23	N
Approved in combination with protective conduit Lloyd's Register	N
Operating temperature	-40 - +105°C

Packaging

Inner Quantity	20
Outer Quantity	20
Outer Dimensions (inches)	11.811x7.874x8.661
Weight Uom	0.01 lbs. Each

Header

3D Model	Available on Website
----------	----------------------

For further technical assistance, please contact us...

Thomas & Betts - USA
860 Ridge Lake Blvd.
Memphis, TN 38120
www.tnb.com

T&B Technical Support
MS 3B-50
860 Ridge Lake Blvd.
Memphis, TN 38120

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com