



Flexible Conduits & Fittings

T&B Catalog Number:

NVWV-M202-10

UPC Number:

78620996615

Status:

Active

Description:

PMAFIX 90 degree black elbow with metric threads. Elbow material - polyamide 6, thread material - nickel plated brass. Thread size - M20 x 1.5, thread length - 10, conduit size NW - 12.

Application

For use in the heavy machine and railway vehicle construction sectors where increased demands are made of the system properties

Characteristics

Self-extinguishing, free from halogens and cadmium

Excellent impact strength

Extremely high thread and system connection strength

Easy installation with the oval clip guarantees and excellent connection to PMAFLEX conduits

Retaining clips offer high pull-out strength values.

Fits both conduit profiles - Fine (T) and coarse (G)

General

Material Polyamide 6

Color Black

Thread Type Metric

Compatible With PMAFLEX

Dimension Information

Fits to Conduit Size (NW) 12

Fits to Conduit Size (metric) 16

Fits to Conduit Size (inches) 3/8

Thread Length (mm) 10.0

Thread Size (Metric) M20 x 1.5

Technical Information

Temperature Range-Continuous (Celsius) -40 degree C - +105 degree C

Temperature-Short-Term (Celsius) +160 degree C

Technical Data Sheet Available on Website

Chemical Resistance Chart Available on Website

Specifications

3dmodel Available on Website

IP Ratings

IP Rating IP68 stat./IP67 dyn.

Packaging

T&B Order Multiple 50

T&B Inner Pack 50

Package in Units 300

T&B Sold in UOM Each

T&B Weight Per UOM 0.06 lbs. Each

Application Support

PMA Reference Guide	Available on Website
Product Overview-PMAFIX Connectors	Available on Website
PMAFIX Connectors-Safety and Sealing Systems	Available on Website

Certifications

RoHS Compliance	Yes
-----------------	-----

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com