

Flexible Conduit Support Systems T&B Catalog Number:

SFH-10-0

UPC Number: 78620996940

Status: Active

Description:

PMACLIP one-piece grey system support with safety lid. Material - polyamide 6, fits to conduit size NW - 10, metric - 12.

polyamide 6, fits to conduit size	e NVV - 10, metric - 12.
Application	
	Designed for fixation of PMAFLEX conduits.
	Machine building and installation applications.
Characteristics	, , , , , , , , , , , , , , , , , , ,
	One-piece construction
	Very high impact resistance
	Optimal axial strain relief due to integrated rib
	Suitable for overhead installation due to safety lid
	High retention forces
	Quick mounting due to single hole fixing
	Very good chemical properties
	Self-extinguishing, free from halogens and cadmi-
	um
	Fits both conduit profiles, fine (T) and coarse (G)
General	
Matarial	Delverside C
Material	Polyamide 6
Color	Grey
Fixing Screw	1 x M5
Suitable for Use With	PMAFLEX, PMA Smart Line Conduits
Dimension Information	
Width (mm)	20.5
Height (mm)	24.5
Depth (mm)	20.0
Technical Information	
Temperature Range-Continuous (Celsi	
Temperature-Short-Term (Celsius)	+160° C
Technical Data Sheet	Available on Website
Chemical Resistance Chart	Available on Website
Specifications	
3dmodel	Available on Website
Packaging	, trailable on trescite
. uo.u.gg	
T&B Order Multiple	100
T&B Inner Pack	100
Package in Units	1000
T&B Sold in UOM	Each
T&B Weight Per UOM	0.03 lbs. Each
Application Support	
PMA Reference Guide	Available on Website
Product Overview-System Supports	Available on Website
Certifications	, transpic on tropone
Co. dilloadono	
RoHS Compliance	Yes



For further technical assistance, please contact us...

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com