HUBBELL
Wiring Device-Kellems

Flush Duplex Series, Flush Service Fitting, Brass

By Hubbell Wiring Device-Kellems
Catalog # FRFBRS2A

Flush Duplex Series, Flush Service Fitting, Brass



Features

- Complete 3" Fire-Rated Poke-Through
- Prewired 20A Duplex Receptacle
- (2) Low Voltage Cable Ports
- Non-metallic Cover with Painted Aluminum Flange

Specifications

Industry Standard(s)	• cULus Listed • UL 514A Listed

Configuration

Knockouts	Duplex Flip Covers and (2) 1/2" Diameter Holes for Low Voltage Wiring
Number Of Outlets	(1) Duplex Opening and (2) 1/2" Diameter Holes for Low Voltage Wiring

Dimensions

Weight	2.95 lb.

General

Specifications	• Carpet Flange - Painted Cast Aluminum/Solid Brass, Brushed and Lacquered • Cover Material - Thermoplastic • Floor thickness - 2 1/4 in. to 7 in. (57.2 to 177.8) • Housing - Engineered flame-retardant thremoplastic • Jack(s) - Low voltage Knockouts Only
Application - For Use On	Carpet/Tile
UPC	783585396149
Material - Mounting Hardware	Mounting Hardware Included
Item Type	3" Fire-Rated Poke Through Component
Finish Type	Brass

Logistics

Carton Quantity	10

Product Assets

Catalog [English]
Catalog Page [English]
Installation Manual [Spanish, French, English]

© 2026 Hubbell Incorporated. All rights reserved