

Kellems Wire Management, Liquidtight
System, Non-Metallic PolyTuff® I Conduit,
Gray, 3/8", 100 feet

By Hubbell Wiring Device-Kellems
Catalog # [G1038](#)

Kellems Wire Management, Liquidtight System, Non-Metallic
PolyTuff® I Conduit, Gray, 3/8", 100 feet

Features

- No jagged metal edges
- Rigid PVC core bonded to flexible PVC jacket
- Non-metallic construction ends metal fatigue and separation problems

Application

UL1660

Specifications

Standards - RoHS Compliance	CM
Status	
EU RoHS Indicator	Yes
Industry Standard(s)	• Meets Requirements Of NEC • UL Listed 1660. Approved For Outdoor And Direct Burial

Current

Voltage Rating	600 V
----------------	-------

Dimensions

Length	100 ft
Trade Size	3/8
Width	0.70 in



Force Related

Load Capacity	Extra Flexible
---------------	----------------

General

Color	Gray
Specifications	• Bend Radius Inches (mm) - 2.00" (50.8) • Conduit ID/OD Inches (mm) - .49"/.70" (12.6/17.8) • Material - Co-extruded rigid and flexible PVC • Trade Size - 3/8 Inch
UPC	783585497983
Type	PolyTuff® I Liquidtight Conduit
Material	Co-extruded rigid and flexible PVC

Logistics

Pallet Quantity	2000
Carton Quantity	100

Product Assets

- [Catalog \[English\]](#)
[Catalog Page \[English\]](#)