

Metal PlugTrak, 40", 15A 6 Receptacle, 6'
Cord and Plug, Gray

By Hubbell Wiring Device-Kellems
Catalog # [HBL20C215GY](#)

Metal PlugTrak, 40", 15A 6 Receptacle, 6' Cord and Plug, Gray



Features

- Multiple spacing configurations
- Gray or ivory scratch resistant finish
- Insulation displacement wiring provides superior wire retention

Performance

Electrical - Receptacle Rating - NEMA 5-15R and NEMA 5-20R,
Mechanical - Wire - #12 AWG Stranded Copper

Specifications

Industry Standard(s)	• CSA Standard C22.2 no. 62 • E253976 /E253830 /E253833 • UL Standard UL 5
EU RoHS Indicator	Contact Manufacturer

Conductor

Wire Size	#12 AWG THHN
-----------	--------------

Configuration

Number Of Receptacles	6
-----------------------	---

Current

Current / Amperage Rating	15 A
---------------------------	------

Dimensions

Length	40 in
--------	-------

General

Specifications	• Number of Receptacles - 6 Receptacles • PlugTrak Amperage - 15A • PlugTrak Length - 40 Inch • Receptacle Face - Thermoplastic • Spacing - 6 Foot Cord Length • Wiring Type - Portable
Color	Gray
Style	Portable
UPC	783585214481
Type	Single Circuit
Item Type	Pre-Wired PlugTrak
Series	Metal

Logistics

Carton Quantity	2
-----------------	---

Product Assets

- [Catalog \[English\]](#)
[Catalog Page \[English\]](#)
[Catalog Page \[English\]](#)
[Installation Manual \[French, English\]](#)