HUBBELL
Wiring Device-Kellems

Kellems Wire Management, Liquidtight System, PolyTuff® Non-Metallic Liquidtight Fittings, 90 Degree Male Liquid-Tight Connector, 3/8", Black



By Hubbell Wiring Device-Kellems
Catalog # P0389NBK

Kellems Wire Management, Liquidtight System, PolyTuff® Non-Metallic Liquidtight Fittings, 90 Degree Male Liquid-Tight Connector, 3/8", Black

Features

- Nylon compression nut has a tapered dome to tighten ferrule onto conduit
- Neoprene O-ring provides liquidtight seal
- Non integral ferrule provides conduit seal and pullout protection

Application

Fittings are to be used with PolyTuff® I and PolyTuff® II

Performance

Environmental - Flammability - UL 94X-2, Environmental - Operating Temperature - –30°F to +225°F (–34°C to +107°C)

Specifications

Industry Standard(s)	• CSA Certified • UL Listed:UL50 Type 4X, 12 and 13

Dimensions

Trade Size	3/8
Dimension - L Length Overall mm	2.91 in
Weight	0.05 lb.
Height	1.98 in
Dimension - Thread Size	1/2" NPT

General

Color	Black
Style	90°
Product Type	PolyTuff® Fittings
Specifications	• Fitting - Nylon • Lockwasher - Zinc plated steel • Sealing Ring - Elastomer
UPC	783585334141
Type	PolyTuff® Non-Metallic Liquidtight Fittings
Material	Nylon

Logistics

Carton Quantity	25

Product Assets

Catalog [English]
Catalog Page [English]

© 2026 Hubbell Incorporated. All rights reserved