HUBBELL
Wiring Device-Kellems

Kellems Wire Management, Liquidtight System, PolyTuff® 90 Degree Male Liquid-Tight Connector, 1", Non-Metallic, Gray

By Hubbell Wiring Device-Kellems
Catalog # P1009NGY



Kellems Wire Management, Liquidtight System, PolyTuff® 90 Degree Male Liquid-Tight Connector, 1", Non-Metallic, Gray

Features

- Nylon compression nut has a tapered dome to tighten ferrule onto conduit
- Neoprene O-ring provides liquidtight seal
- Non integral ferrule provides conduit seal and pullout protection

Application

Fittings are to be used with PolyTuff® I and PolyTuff® II

Specifications

Standards - RoHS Compliance Status	CM
EU RoHS Indicator	Yes
Industry Standard(s)	• CSA Certified • UL Listed:UL50 Type 4X, 12 and 13

Dimensions

Trade Size	1
Height	2.83 in
Dimension - Thread Size	1" NPT

General

Color	Gray
Style	90°
Specifications	• Fitting - Nylon • Lockwasher - Zinc plated steel • Sealing Ring - Elastomer
UPC	783585810041
Type	PolyTuff® Non-Metallic Liquidtight Fittings
Material	Nylon

Logistics

Pallet Quantity	2160
Carton Quantity	10

Product Assets

Catalog [English]
Catalog Page [English]

© 2026 Hubbell Incorporated. All rights reserved