
HUBBELL
Wiring Device-Kellems

Non-Metallic Raceway, BaseTrak, 2 or 3 Channel, External Elbow, Base and Cover



By Hubbell Wiring Device-Kellems
Catalog # PB3EEBCA

Non-Metallic Raceway, BaseTrak, 2 or 3 Channel, External Elbow, Base and Cover

Features

- Full capacity 1¼ in. bend radius external elbow

Application

External Elbow Base and Cover

Performance

Environmental - Flame Rating - UL94V-0, Environmental - Temperature Range - -25.6° to 158° F

Specifications

Standards - RoHS Compliance Status	CM
EU RoHS Indicator	Contact Manufacturer
Industry Standard(s)	UL 5A

General

Color	Office White
Style	External
Sub Brand	Non-Metallic Raceway
Series	• PB2 • PB3
Specifications	• Crush Resistance - 300 lbs. • Impact Resistance - 5 ft. lbs. • Material - UV Stabilized PVC
UPC	783585310084
Type	Elbows
Item Type	PB2 and PB3 BaseTrak Series
Material	Non-Metallic
Cover Type	Removable

Logistics

Carton Quantity	10

Product Assets

Catalog [English]
Catalog Page [English]
Catalog Page [English]
Installation Manual [Spanish, French, English]

© 2026 Hubbell Incorporated. All rights reserved