



## 3/4 in. Rigid/IMC Bushing, Insulated

By Raco  
Catalog # 1133

3/4 in. Rigid/IMC Bushing, Insulated



\*Representative Image

### Features

- Malleable iron construction ensures mechanical protection
- Zinc-electroplated for added corrosion protection
- Insuliner rated for 150° C
- Available in die-cast zinc (Add DC to end of catalog number when ordering)
- UL and CSA Listed
- Available in trade sizes of 1/2 in. through 4 in.

### General

Conduit Type	Rigid/IMC
EU RoHS Indicator	Contact Manufacturer
Fitting Type	Bushings
Insulation Type	Insulated
Item Type	4D
Material	Malleable Iron
UPC	050169011331

### Dimensions

Dimensions	0.563 in x 1.406 in x 1.406 in
Height	1.406 in
Length	0.563 in
Trade Size	3/4 in
Weight	0.077 lb
Width	1.406 in

### Certifications And Compliance

Certified Listed	<ul style="list-style-type: none"><li>• UL Listed</li><li>• CSA Certified</li></ul>
------------------	---

Industry Standard(s)	UL 514B
----------------------	---------

### Logistics

Carton Quantity	50
Pallet Quantity	31500

### Product Assets

<a href="#">Catalogs - RACO / TayMac / Bell Full Catalog</a>
<a href="#">Product Logo - Conduit</a>
<a href="#">SDS - HCC_SDS</a>
<a href="#">Terms and Conditions - HCC Terms &amp; Conditions</a>



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.  
RACO-1133-SPEC-EN | REV 6/2024