



## 1 in. Rigid/IMC Bushing, Insulated

By Raco  
Catalog # 1134

1 in. Rigid/IMC Bushing, Insulated



\*Representative Image

### Features

- Malleable iron construction ensures mechanical protection
- Zinc-electroplated for added corrosion protection
- Insuliner rated for 150° C
- Available in die-cast zinc (Add DC to end of catalog number when ordering)
- UL and CSA Listed
- Available in trade sizes of 1/2 in. through 4 in.

### General

Conduit Type	Rigid/IMC
EU RoHS Indicator	Contact Manufacturer
Fitting Type	Bushings
Insulation Type	Insulated
Material	Malleable Iron
UPC	050169011348

### Dimensions

Dimensions	0.656 in x 1.75 in x 1.75 in
Height	1.75 in
Length	0.656 in
Trade Size	1 in
Weight	0.067 lb
Width	1.75 in

### Certifications And Compliance

Certified Listed	<ul style="list-style-type: none"><li>• UL Listed</li><li>• CSA Certified</li></ul>
------------------	---

Industry Standard(s)	UL 514B
----------------------	---------

### Logistics

Carton Quantity	25
Minimum Pack Quantity	25
Pallet Quantity	15750

### Product Assets

Catalogs - RACO / TayMac / Bell Full Catalog
Product Logo - Conduit
SDS - HCC_SDS
Terms and Conditions - HCC Terms & Conditions



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.  
RACO-1134-SPEC-EN | REV 6/2024