



## 3/4 in. Rigid/IMC Hub

By Raco  
Catalog # 1703

3/4 in. Rigid/IMC Hub



\*Representative Image

### Features

- Rugged metallic construction ensures mechanical protection
- Insulated throat protects wires and reduces pulling effort
- O-ring secures the assembly and provides a raintight seal.
- UL Listed, CSA
- Available in trade sizes 1/2 in. through 4 in.

### General

Conduit Type	Rigid/IMC
EU RoHS Indicator	Contact Manufacturer
Environmental Conditions	Wet Location
Fitting Type	Hubs
Insulation Type	Insulated
Material	Die Cast Zinc
UPC	050169017036

### Dimensions

Dimensions	1.473 in x 1.685 in x 1.685 in
Height	1.685 in
Length	1.473 in
Trade Size	3/4 in
Weight	0.259 lb
Width	1.685 in

### Certifications And Compliance

Certified Listed	<ul style="list-style-type: none"><li>• UL Listed</li><li>• CSA Certified</li></ul>
Industry Standard(s)	UL 514B

### Logistics

Carton Quantity	25
Minimum Pack Quantity	25
Pallet Quantity	8375

### Product Assets

<a href="#">Brochures - HCC Products for Solar</a>
<a href="#">Catalogs - RACO / TayMac / Bell Full Catalog</a>
<a href="#">Product Logo - Conduit</a>
<a href="#">SDS - HCC_SDS</a>
<a href="#">Terms and Conditions - HCC Terms &amp; Conditions</a>



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.  
RACO-1703-SPEC-EN | REV 6/2024