



1/2 in. Rigid/IMC Compression Connector, Uninsulated

By Raco
Catalog # 1802

1/2 in. Rigid/IMC Compression Connector, Uninsulated



Features

- All steel/malleable iron construction ensures mechanical protection for the raceway
- Zinc-electroplated for added corrosion protection
- Noninsulated
- Hex compression nuts assure easy wrench installation
- UL Listed, CSA
- Available in trade sizes 1/2 in. through 4 in.

General

Conduit Type	Rigid/IMC
Connector Type	Compression
EU RoHS Indicator	Yes
Fitting Type	Connectors
Material	Steel/Malleable Iron
UPC	050169018026

Dimensions

Dimensions	1.406 in x 1.063 in x 1.063 in
Height	1.063 in
Length	1.406 in
Trade Size	1/2 in
Weight	0.118 lb
Width	1.063 in

Certifications And Compliance

Certified Listed

- UL Listed
- CSA Certified

Industry Standard(s)

UL 514B

Logistics

Carton Quantity	25
Minimum Pack Quantity	25
Pallet Quantity	10500

Product Assets

[Catalogs - RACO / TayMac / Bell Full Catalog](#)
[Certifications - UL COC - E195969-1](#)
[Product Logo - Conduit](#)
[Sales Drawings - 1802](#)
[SDS - HCC_SDS](#)
[Terms and Conditions - HCC Terms & Conditions](#)



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.
RACO-1802-SPEC-EN | REV 6/2024