



4 in. Rigid/IMC Compression Connector, Uninsulated

By Raco
Catalog # 1816

4 in. Rigid/IMC Compression Connector, Uninsulated



Features

- Malleable iron construction ensures mechanical protection for the raceway
- Zinc-electroplated for added corrosion protection
- Noninsulated
- Hex compression nuts assure easy wrench installation
- UL Listed, CSA
- Available in trade sizes 1/2 in. through 4 in.

General

Conduit Type	Rigid/IMC
Connector Type	Compression
EU RoHS Indicator	Contact Manufacturer
Fitting Type	Connectors
Material	Steel/Malleable Iron
UPC	050169018163

Dimensions

Dimensions	4.5 in x 5.906 in x 5.906 in
Height	5.906 in
Length	4.5 in
Trade Size	4 in
Weight	4.45 lb
Width	5.906 in

Certifications And Compliance

Certified Listed

- UL Listed
- CSA Certified

Industry Standard(s)

UL 514B

Logistics

Carton Quantity	1
Minimum Pack Quantity	1
Pallet Quantity	336

Product Assets

[Catalogs - RACO / TayMac / Bell Full Catalog](#)
[Customer Notices - Prop65_Cancer](#)
[Product Logo - Conduit](#)
[Sales Drawings - 1816](#)
[SDS - HCC_SDS](#)
[Terms and Conditions - HCC Terms & Conditions](#)



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.
RACO-1816-SPEC-EN | REV 6/2024