



## 1/2 in. Flex Straight Squeeze Connector, Uninsulated

By Raco  
Catalog # [2102](#)

1/2 in. Flex Straight Squeeze Connector, Uninsulated



\*Representative Image

### Features

- All malleable construction ensures mechanical protection for the raceway
- Electro zinc plated for added corrosion protection
- UPC bar coded fittings are individually polybagged with a preprinted UPC-A bar code and packaged in pre-scored tear top cartons for an attractive presentation
- Additional sizes available

### General

Catalog Number	2102
Conduit Type	Flexible Metal Conduit
Connector Type	Squeeze
EU RoHS Indicator	Yes
Fitting Type	Connectors
Material	Malleable Iron
UPC	050169021026

### Dimensions

Dimensions 1.516 in x 1.22 in x 1.625 in

Height	1.625 in
Length	1.516 in
Trade Size	1/2 in
Weight	0.148 lb
Width	1.22 in

### Certifications And Compliance

Buy America(n) Qualified [Contact Manufacturer](#)  
Certified Listed cULus Listed

### Logistics

Carton Quantity	50
Pallet Quantity	15000

### Product Assets

[Catalogs - RACO / TayMac / Bell Full Catalog](#)

[Catalogs - Commercial Fittings](#)

[SDS - HCC SDS](#)

[Specifications - 2102](#)

[Terms and Conditions - HCC Terms & Conditions](#)



A Hubbell brand

©2025 Hubbell Incorporated. All rights reserved  
RACO-2102-SPEC-EN | REV 3/2025