



## 3/4 in. Flex Screw-In Connector

By Raco  
Catalog # 2283

3/4 in. Flex Screw-In Connector



\*Representative Image

### Features

- Rugged metallic construction ensures mechanical protection for the raceway
- Additional sizes available

### General

Conduit Type	Flexible Metal Conduit
Connector Type	Screw-In
EU RoHS Indicator	Contact Manufacturer
Fitting Type	Connectors
Insulation Type	Uninsulated
Material	Die Cast Zinc
UPC	050169022832

### Dimensions

Dimensions	1.625 in x 1.125 in x 1.125 in
Height	1.125 in
Length	1.625 in
Trade Size	3/4 in
Weight	0.093 lb
Width	1.125 in

### Certifications And Compliance

Certified Listed	<ul style="list-style-type: none"><li>• UL Listed</li><li>• CSA Certified</li></ul>
------------------	---

Industry Standard(s)	UL 514B
----------------------	---------

### Logistics

Carton Quantity	250
Minimum Pack Quantity	25
Pallet Quantity	10000

### Product Assets

<a href="#">Brochures - HCC Products for Solar</a>
<a href="#">Catalogs - RACO / TayMac / Bell Full Catalog</a>
<a href="#">SDS - HCC_SDS</a>
<a href="#">Terms and Conditions - HCC Terms &amp; Conditions</a>



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.  
RACO-2283-SPEC-EN | REV 6/2024