



2 in. Rigid/IMC or EMT Service Entrance Head

By Raco
Catalog # 2408

2 in. Rigid/IMC or EMT Service Entrance Head



*Representative Image

Features

- Lightweight aluminum body construction eases installation and provides corrosion resistance
- Plastic insulator snaps out easily for quick cable insertion
- Listed for use in wet locations
- Additional sizes available

General

Conduit Type	Service Entrance
Connector Type	Clamp-Type
EU RoHS Indicator	Contact Manufacturer
Fitting Type	Clamps
Material	Aluminum
UPC	050169024089

Dimensions

Dimensions	4.375 in x 4.25 in x 5.875 in
Height	5.875 in
Insulating Hole Diameter	<ul style="list-style-type: none">3 Holes 1 Dia in2 Holes 0.750 Dia in1 Hole 0.531 Dia in
Length	4.375 in
Trade Size	2 in
Weight	1.082 lb
Width	4.25 in

Certifications And Compliance

Certified Listed	UL Listed
Industry Standard(s)	UL 514B
Nema Rating	NEMA 3R

Logistics

Carton Quantity	5
Minimum Pack Quantity	5
Pallet Quantity	300

Product Assets

Catalogs - RACO / TayMac / Bell Full Catalog
Certifications - UL COC - E195973-1
Customer Notices - Prop 65 - Cancer & Reproductive Harm Notice
Product Logo - SE CABLE
SDS - HCC_SDS
Terms and Conditions - HCC Terms & Conditions



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.
RACO-2408-SPEC-EN | REV 6/2024