



Concrete Ring, Welded, 4 in. Deep, Double Row 1/2 & 3/4 in. KO's

By Raco
Catalog # 274

Concrete Ring, Welded, 4 in. Deep, Double Row 1/2 & 3/4 in. KO's



Features

- Flat sides provide excellent contact for locknuts
- External ears are used to nail the ring to the wood form
- Top cover is removable for before-pour work
- Ears on inside of box are for fixtures
- Waxed fixture ears prevent concrete from interfering with the threads
- A variety of covers are available
- Cover plate must be ordered separately with all RACO® concrete rings
- Used in high-rise construction
- 61.5 cu. in. capacity
- Not designed for ceiling fan support, the maximum support load for a static fixture is 50 lbs

General

Catalog Number	274
Color	Gray
Drawn or Welded	Welded
EU RoHS Indicator	Contact Manufacturer
Knockouts	1/2 in; 3/4 in
Material	Steel
Type	Concrete Ring
UPC	050169002742
Wiring System	Conduit

Dimensions

Cubic Capacity	49.3 cu.in
Depth	4 in
Fixture Lbs.	50 lb
Height	4 in
Weight	1.03 lb
Width	4 in

Certifications And Compliance

Buy America(n) Qualified	TAA Compliant (All status valid till December 2024)
Certified Listed	UL Listed

Logistics

Carton Quantity	20
Packaging Type	No Packaging
Pallet Quantity	1000

Product Assets

Catalogs - Steel Boxes, Covers and Accessories
Catalogs - RACO / TayMac / Bell Full Catalog
Certifications - LEED Statement
Certifications - NEMA OS1
Sales Drawings - 274 Customer Drawing
SDS - HCC SDS
Specifications - 274
Terms and Conditions - HCC Terms & Conditions



A Hubbell brand