



1/2 in. EMT Raintight Compression Coupling

By Raco
Catalog # 2922RT

1/2 in. EMT Raintight Compression Coupling

Features

- Steel construction ensures mechanical protection
- Zinc-electroplated for added corrosion protection
- Marked with "Wet Location" for easy inspection
- cULus
- Available in trade sizes of 1/2 in. through 4 in.

General

Catalog Number	2922RT
Conduit Type	EMT
Connector Type	Compression
EU RoHS Indicator	Contact Manufacturer
Environmental Conditions	Wet Location
Fitting Type	Couplings
Material	Steel
UPC	050169292297

Dimensions

Dimensions	2.078 in x 1.05 in x 1.12 in
Height	1.12 in
Length	2.078 in
Trade Size	1/2 in



*Representative Image

Weight	0.125 lb
Width	1.05 in

Certifications And Compliance

Buy America(n) Qualified	Contact Manufacturer
Certified Listed	cULus Listed
Industry Standard(s)	UL 514B

Logistics

Carton Quantity	250
Pallet Quantity	15000

Product Assets

[Brochures - HCC Products for Solar](#)
[Catalogs - RACO / TayMac / Bell Full Catalog](#)
[Catalogs - Commercial Fittings](#)
[Certifications - UL COC - E195970 - 2](#)
[Product Logo - Conduit](#)
[Sales Drawings - 2922RT-CHINA Customer Drawing](#)
[SDS - HCC SDS](#)
[Sell Sheets - Raintight Steel EMT Compression Fittings](#)
[Specifications - 2922RT](#)
[Terms and Conditions - HCC Terms & Conditions](#)



A Hubbell brand