



1/2 in. Flex Straight Squeeze Connector, Insulated

By Raco
Catalog # 3302

1/2 in. Flex Straight Squeeze Connector, Insulated



Features

- All malleable construction ensures mechanical protection for the raceway
- Electro zinc plated for added corrosion protection
- UPC bar coded fittings are individually polybagged with a preprinted UPC-A bar code and packaged in pre-scored tear top cartons for an attractive presentation
- Additional sizes available

General

Catalog Number	3302
Conduit Type	Flexible Metal Conduit
Connector Type	Squeeze
EU RoHS Indicator	Contact Manufacturer
Fitting Type	Connectors
Insulation Type	Insulated
Material	Malleable Iron
UPC	050169033029

Dimensions

Dimensions	1.36 in x 1.125 in x 1.625 in
Height	1.625 in
Length	1.36 in
Trade Size	1/2 in
Weight	0.148 lb
Width	1.125 in

Certifications And Compliance

Certified Listed	cULus Listed
------------------	--------------

Logistics

Carton Quantity	50
Pallet Quantity	19500

Product Assets

Catalogs - RACO / TayMac / Bell Full Catalog
SDS - HCC_SDS
Terms and Conditions - HCC Terms & Conditions



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.
RACO-3302-SPEC-EN | REV 6/2024