



3/4 in. Flex Straight Squeeze Connector, Insulated

By Raco
Catalog # 3303

3/4 in. Flex Straight Squeeze Connector, Insulated



Features

- All malleable construction ensures mechanical protection for the raceway
- Electro zinc plated for added corrosion protection
- UPC bar coded fittings are individually polybagged with a preprinted UPC-A bar code and packaged in pre-scored tear top cartons for an attractive presentation
- Additional sizes available

General

Conduit Type	Flexible Metal Conduit
Connector Type	Squeeze
EU RoHS Indicator	Contact Manufacturer
Fitting Type	Connectors
Insulation Type	Insulated
Item Type	4D
Material	Malleable Iron
UPC	050169033036

Dimensions

Dimensions	1.469 in x 1.38 in x 1.938 in
Height	1.938 in
Length	1.469 in
Trade Size	3/4 in
Weight	0.228 lb
Width	1.38 in

Certifications And Compliance

Certified Listed cULus Listed

Logistics

Carton Quantity	25
Minimum Pack Quantity	25
Pallet Quantity	14400

Product Assets

[Catalogs - RACO / TayMac / Bell Full Catalog](#)
[Customer Notices - Prop 65 Notice](#)
[SDS - HCC_SDS](#)
[Terms and Conditions - HCC Terms & Conditions](#)



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.
RACO-3303-SPEC-EN | REV 6/2024