



## 2 in. Flex Straight Squeeze Connector, Insulated

By Raco  
Catalog # 3308

2 in. Flex Straight Squeeze Connector, Insulated



\*Representative Image

### Features

- All malleable construction ensures mechanical protection for the raceway
- Electro zinc plated for added corrosion protection
- UPC bar coded fittings are individually polybagged with a preprinted UPC-A bar code and packaged in pre-scored tear top cartons for an attractive presentation
- Additional sizes available

### General

Catalog Number	3308
Conduit Type	Flexible Metal Conduit
Connector Type	Squeeze
EU RoHS Indicator	Contact Manufacturer
Fitting Type	Connectors
Insulation Type	Insulated
Material	Malleable Iron
UPC	050169033081

### Dimensions

Dimensions	2.75 in x 2.891 in x 3.344 in
Height	3.344 in
Length	2.75 in
Trade Size	2 in
Weight	1.082 lb
Width	2.891 in

### Certifications And Compliance

Certified Listed	cULus Listed
------------------	--------------

### Logistics

Carton Quantity	10
Minimum Pack Quantity	10
Pallet Quantity	3000

### Product Assets

Catalogs - RACO / TayMac / Bell Full Catalog
Customer Notices - Prop 65 Notice
SDS - HCC_SDS
Terms and Conditions - HCC Terms & Conditions



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.  
RACO-3308-SPEC-EN | REV 6/2024