



## 1-1/4 in. Liquidtight Straight Connector, Uninsulated

By Raco  
Catalog # 3405

1-1/4 in. Liquidtight Straight Connector, Uninsulated



\*Representative Image

### Features

- Use with flexible metallic liquidtight conduit and Type B flexible nonmetallic liquidtight conduit
- Zinc-electroplated for added corrosion protection
- Noninsulated
- Innovative split gland-ring assures a perfect seal, preventing pullouts
- Available in trade sizes 3/8 in. through 4 in.
- Sealing washer and heavy-duty locknut included
- All components are reusable

### General

Conduit Type	Liquidtight
EU RoHS Indicator	Contact Manufacturer
Environmental Conditions	Wet Location
Fitting Type	Connectors
Insulation Type	Uninsulated
Material	Steel/Malleable Iron
UPC	050169034057

### Dimensions

Dimensions	2.438 in x 2.438 in x 2.188 in
Height	2.188 in
Length	2.438 in
Trade Size	1-1/4 in
Weight	0.635 lb
Width	2.438 in

### Certifications And Compliance

Certified Listed	<ul style="list-style-type: none"><li>• UL Listed</li><li>• CSA Certified</li></ul>
Hazardous Rating(s)	<ul style="list-style-type: none"><li>• Class I, Division 2</li><li>• Class II Division 1 &amp; 2</li><li>• Class III, Division 1 &amp; 2</li></ul>
Industry Standard(s)	UL 514B

### Logistics

Carton Quantity	10
Minimum Pack Quantity	10
Pallet Quantity	2700

### Product Assets

Catalogs - RACO / TayMac / Bell Full Catalog
Product Logo - LT COND
Sales Drawings - 3405
SDS - HCC_SDS
Terms and Conditions - HCC Terms & Conditions



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.  
RACO-3405-SPEC-EN | REV 6/2024