



## 1/2 in. 90 Degree Liquidtight Connector, Uninsulated

By Raco  
Catalog # 3422

1/2 in. 90 Degree Liquidtight Connector, Uninsulated



\*Representative Image

### Features

- Use with flexible metallic liquidtight conduit and Type B flexible nonmetallic liquidtight conduit
- Zinc-electroplated for added corrosion protection
- Noninsulated
- Innovative split gland-ring assures a perfect seal, preventing pullouts
- Available in trade sizes 3/8 in. through 4 in.
- Sealing washer and heavy-duty locknut included
- All components are reusable

### General

Conduit Type	Liquidtight
EU RoHS Indicator	Yes
Environmental Conditions	Wet Location
Fitting Type	Connectors
Insulation Type	Uninsulated
Material	Steel/Malleable Iron
UPC	050169034224

### Dimensions

Dimensions	1.17 in x 2.358 in x 2.084 in
Height	2.084 in
Length	1.17 in
Trade Size	1/2 in
Weight	0.264 lb
Width	2.358 in

### Certifications And Compliance

Certified Listed	<ul style="list-style-type: none"><li>• UL Listed</li><li>• CSA Certified</li></ul>
Hazardous Rating(s)	<ul style="list-style-type: none"><li>• Class I, Division 2</li><li>• Class II Division 1 &amp; 2</li><li>• Class III, Division 1 &amp; 2</li></ul>
Industry Standard(s)	UL 514B

### Logistics

Carton Quantity	100
Minimum Pack Quantity	25
Pallet Quantity	6400

### Product Assets

<a href="#">Catalogs - RACO / TayMac / Bell Full Catalog</a>
<a href="#">Product Logo - LT COND</a>
<a href="#">Sales Drawings - 3422</a>
<a href="#">SDS - HCC_SDS</a>
<a href="#">Terms and Conditions - HCC Terms &amp; Conditions</a>
<a href="#">Video - RACO: Liquidtight Connectors vs. popular competitor</a>



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.  
RACO-3422-SPEC-EN | REV 6/2024