



3/4 in. 90 Degree Liquidtight Connector, Uninsulated

By Raco
Catalog # 3423

3/4 in. 90 Degree Liquidtight Connector, Uninsulated



*Representative Image

Features

- Use with flexible metallic liquidtight conduit and Type B flexible nonmetallic liquidtight conduit
- Zinc-electroplated for added corrosion protection
- Noninsulated
- Innovative split gland-ring assures a perfect seal, preventing pullouts
- Available in trade sizes 3/8 in. through 4 in.
- Sealing washer and heavy-duty locknut included
- All components are reusable

General

| | |
|--------------------------|----------------------|
| Conduit Type | Liquidtight |
| EU RoHS Indicator | Yes |
| Environmental Conditions | Wet Location |
| Fitting Type | Connectors |
| Insulation Type | Uninsulated |
| Material | Steel/Malleable Iron |
| UPC | 050169034231 |

Dimensions

| | |
|------------|-----------------------------|
| Dimensions | 1.4 in x 2.76 in x 2.398 in |
| Height | 2.398 in |
| Length | 1.4 in |
| Trade Size | 3/4 in |
| Weight | 0.364 lb |
| Width | 2.76 in |

Certifications And Compliance

| | |
|----------------------|---|
| Certified Listed | <ul style="list-style-type: none">• UL Listed• CSA Certified |
| Hazardous Rating(s) | <ul style="list-style-type: none">• Class I, Division 2• Class II Division 1 & 2• Class III, Division 1 & 2 |
| Industry Standard(s) | UL 514B |

Logistics

| | |
|-----------------------|------|
| Carton Quantity | 100 |
| Minimum Pack Quantity | 25 |
| Pallet Quantity | 6000 |

Product Assets

| |
|---|
| Catalogs - RACO / TayMac / Bell Full Catalog |
| Product Logo - LT COND |
| Sales Drawings - 3423 |
| SDS - HCC_SDS |
| Terms and Conditions - HCC Terms & Conditions |
| Video - RACO: Liquidtight Connectors vs. popular competitor |



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.
RACO-3423-SPEC-EN | REV 6/2024