



## 3/8 in. Liquidtight Straight Connector, Insulated with Ground Lug

By Raco

Catalog # [3511-3](#)

3/8 in. Liquidtight Straight Connector, Insulated with Ground Lug



\*Representative Image

### Features

- Steel construction ensures mechanical protection
- All metallic components are zinc electroplated for added corrosion protection
- Insulated with ground lug
- Patented split gland-ring assures a perfect seal, preventing pullouts
- UL Listed, CSA
- Available in trade sizes 3/8 in. through 4 in.
- Sealing washer and heavy-duty locknut included
- All components are reusable

### General

Accessory Type	Fitting
Catalog Number	3511-3
Conduit Type	Liquidtight
Connector Type	Grounding
EU RoHS Indicator	Yes
Environmental Conditions	Wet Location
Fitting Type	Connectors
Insulation Type	Insulated
Material	Steel/Malleable Iron
UPC	050169351130

### Dimensions

Dimensions	1.453 in x 1.063 in x 1.063 in
Height	1.063 in
Length	1.453 in
Trade Size	3/8 in
Weight	0.19 lb
Width	1.063 in

### Electrical Ratings

Grounding Wire Capacity	#4 STR
Maximum	
Grounding Wire Capacity	#14 SOL
Minimum	

### Certifications And Compliance

Buy America(n) Qualified	Contact Manufacturer
Certified Listed	<ul style="list-style-type: none"><li>• UL Listed</li><li>• CSA Certified</li><li>• Class I, Division 2</li><li>• Class II Division 1 &amp; 2</li><li>• Class III, Division 1 &amp; 2</li></ul>
Hazardous Rating(s)	
Industry Standard(s)	UL 514B

### Logistics

Carton Quantity	25
Minimum Pack Quantity	25
Pallet Quantity	7600

### Product Assets

<a href="#">Catalogs - RACO / TayMac / Bell Full Catalog</a>
<a href="#">Catalogs - Commercial Fittings</a>
<a href="#">Certifications - UL COC-E195975-4</a>
<a href="#">Product Logo - LT COND</a>
<a href="#">Sales Drawings - 35113 Customer Drawing</a>
<a href="#">SDS - HCC SDS</a>
<a href="#">Specifications - 35113</a>
<a href="#">Terms and Conditions - HCC Terms &amp; Conditions</a>



A Hubbell brand