



3/4 in. Liquidtight Straight Connector, Insulated

By Raco
Catalog # 3513RAC

3/4 in. Liquidtight Straight Connector, Insulated



*Representative Image

Features

- Use with flexible metallic liquidtight conduit and Type B flexible nonmetallic liquidtight conduit
- Zinc-electroplated for added corrosion protection
- Insulated
- Innovative split gland-ring assures a perfect seal, preventing pullouts
- Available in trade sizes 3/8 in. through 4 in.
- Sealing washer and heavy-duty locknut included
- All components are reusable

General

Conduit Type	Flexible Metal Conduit
EU RoHS Indicator	Contact Manufacturer
Environmental Conditions	Wet Location
Fitting Type	Connectors
Insulation Type	Insulated
Material	Steel
UPC	050169035139

Dimensions

Dimensions	1.625 in x 1.625 in x 1.875 in
Height	1.875 in
Length	1.625 in
Trade Size	3/4 in
Weight	0.243 lb
Width	1.625 in

Certifications And Compliance

Certified Listed	<ul style="list-style-type: none">• UL Listed• CSA Certified
Hazardous Rating(s)	<ul style="list-style-type: none">• Class I, Division 2• Class II Division 1 & 2• Class III, Division 1 & 2
Industry Standard(s)	UL 514B

Logistics

Carton Quantity	100
Minimum Pack Quantity	25
Pallet Quantity	8000

Product Assets

Catalogs - RACO / TayMac / Bell Full Catalog
Product Logo - LT COND
Sales Drawings - 3513RAC
SDS - HCC_SDS
Terms and Conditions - HCC Terms & Conditions
Video - RACO: Liquidtight Connectors vs. popular competitor



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.
RACO-3513RAC-SPEC-EN | REV 6/2024