



1-1/2 in. Liquidtight Straight Connector, Insulated

By Raco
Catalog # 3516



*Representative Image

1-1/2 in. Liquidtight Straight Connector, Insulated

Features

- Use with flexible metallic liquidtight conduit and Type B flexible nonmetallic liquidtight conduit
- Zinc-electroplated for added corrosion protection
- Insulated
- Innovative split gland-ring assures a perfect seal, preventing pullouts
- Available in trade sizes 3/8 in. through 4 in.
- Sealing washer and heavy-duty locknut included
- All components are reusable

General

Conduit Type	Flexible Metal Conduit
EU RoHS Indicator	Contact Manufacturer
Environmental Conditions	Wet Location
Fitting Type	Connectors
Insulation Type	Insulated
Material	3516
UPC	050169035160

Dimensions

Dimensions	2.813 in x 2.813 in x 2.438 in
Height	2.438 in
Length	2.813 in
Trade Size	1-1/2 in
Weight	0.855 lb
Width	2.813 in

Certifications And Compliance

Certified Listed	• UL Listed
	• CSA Certified
Hazardous Rating(s)	• Class I, Division 2
	• Class II Division 1 & 2
	• Class III, Division 1 & 2
Industry Standard(s)	UL 514B

Logistics

Carton Quantity	5
Minimum Pack Quantity	5
Pallet Quantity	2520

Product Assets

- [Catalogs - RACO / TayMac / Bell Full Catalog](#)
- [Product Logo - LT COND](#)
- [Sales Drawings - 3516](#)
- [SDS - HCC_SDS](#)
- [Terms and Conditions - HCC Terms & Conditions](#)
- [Video - RACO: Liquidtight Connectors vs. popular competitor](#)



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.
RACO-3516-SPEC-EN | REV 6/2024