



# 1-1/4 in. 90 Degree Liquidtight Connector, Insulated

By Raco  
Catalog # 3545



1-1/4 in. 90 Degree Liquidtight Connector, Insulated

\*Representative Image

### Features

- Use with flexible metallic liquidtight conduit and Type B flexible nonmetallic liquidtight conduit
- Zinc-electroplated for added corrosion protection
- Insulated
- Innovative split gland-ring assures a perfect seal, preventing pullouts
- Available in trade sizes 3/8 in. through 4 in.
- Sealing washer and heavy-duty locknut included
- All components are reusable

### General

|                          |                      |
|--------------------------|----------------------|
| Conduit Type             | Liquidtight          |
| EU RoHS Indicator        | Contact Manufacturer |
| Environmental Conditions | Wet Location         |
| Fitting Type             | Connectors           |
| Insulation Type          | Insulated            |
| Material                 | Steel/Malleable Iron |
| UPC                      | 050169035450         |

### Dimensions

|            |                               |
|------------|-------------------------------|
| Dimensions | 2.438 in x 2.438 in x 4.25 in |
| Height     | 4.25 in                       |
| Length     | 2.438 in                      |
| Trade Size | 1-1/4 in                      |
| Weight     | 0.985 lb                      |
| Width      | 2.438 in                      |

### Certifications And Compliance

|                      |                                                                                                                                                     |
|----------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------|
| Certified Listed     | <ul style="list-style-type: none"><li>• UL Listed</li><li>• CSA Certified</li></ul>                                                                 |
| Hazardous Rating(s)  | <ul style="list-style-type: none"><li>• Class I, Division 2</li><li>• Class II Division 1 &amp; 2</li><li>• Class III, Division 1 &amp; 2</li></ul> |
| Industry Standard(s) | UL 514B                                                                                                                                             |

### Logistics

|                       |      |
|-----------------------|------|
| Carton Quantity       | 10   |
| Minimum Pack Quantity | 10   |
| Pallet Quantity       | 2000 |

### Product Assets

[Catalogs - RACO / TayMac / Bell Full Catalog](#)  
[Product Logo - LT COND](#)  
[Sales Drawings - 3545](#)  
[SDS - HCC\\_SDS](#)  
[Terms and Conditions - HCC Terms & Conditions](#)  
[Video - RACO: Liquidtight Connectors vs. popular competitor](#)



A proud member of the Hubbell Family.