



1/2 in. 45 Degree Liquidtight Connector, Insulated with Ground Lug

By Raco
Catalog # [3562-3](#)



1/2 in. 45 Degree Liquidtight Connector, Insulated with Ground Lug

Features

- Malleable iron construction of the body and steel nut
- All metallic components are zinc electroplated for added corrosion protection
- Malleable iron castings mate with other components perfectly without strain or distortion
- Patented split gland-ring assures a perfect seal, preventing pullouts
- UL Listed, CSA
- Available in trade sizes 3/8 in. through 2 in.
- Sealing washer and heavy-duty locknut included
- All components are reusable

General

Catalog Number	3562-3
Conduit Type	Liquidtight
Connector Type	Grounding
EU RoHS Indicator	Yes
Environmental Conditions	Wet Location
Fitting Type	Connectors
Insulation Type	Insulated
Material	Steel/Malleable Iron
UPC	050169356234

Dimensions

Dimensions	2.3 in x 1.25 in x 2.188 in
Height	2.188 in

Length	2.3 in
Trade Size	1/2 in
Weight	0.314 lb
Width	1.25 in

Certifications And Compliance

Buy America(n) Qualified Certified Listed	Contact Manufacturer • UL Listed • CSA Certified
Hazardous Rating(s)	• Class I, Division 2 • Class II Division 1 & 2 • Class III, Division 1 & 2
Industry Standard(s)	UL 514B

Logistics

Carton Quantity	25
Minimum Pack Quantity	25
Pallet Quantity	7200

Product Assets

[Catalogs - RACO / TayMac / Bell Full Catalog](#)
[Catalogs - Commercial Fittings](#)
[Certifications - UL COC-E195975-4](#)
[Product Logo - LT COND](#)
[Sales Drawings - 35623 Customer Drawing](#)
[SDS - HCC SDS](#)
[Specifications - 35623](#)
[Terms and Conditions - HCC Terms & Conditions](#)



A Hubbell brand