



3/4 in. 45 Degree Liquidtight Connector, Insulated with Ground Lug

By Raco
Catalog # 3563-3



3/4 in. 45 Degree Liquidtight Connector, Insulated with Ground Lug

Features

- Malleable iron construction of the body and steel nut
- All metallic components are zinc electroplated for added corrosion protection
- Malleable iron castings mate with other components perfectly without strain or distortion
- Patented split gland-ring assures a perfect seal, preventing pullouts
- UL Listed, CSA
- Available in trade sizes 3/8 in. through 2 in.
- Sealing washer and heavy-duty locknut included
- All components are reusable

General

Catalog Number	3563-3
Conduit Type	Liquidtight
Connector Type	Grounding
EU RoHS Indicator	Yes
Environmental Conditions	Wet Location
Fitting Type	Connectors
Insulation Type	Insulated
Material	Steel/Malleable Iron
UPC	050169356333

Dimensions

Dimensions	2.8 in x 1.407 in x 2.359 in
Height	2.359 in

Length	2.8 in
Trade Size	3/4 in
Weight	0.423 lb
Width	1.407 in

Certifications And Compliance

Buy America(n) Qualified Certified Listed	Contact Manufacturer • UL Listed • CSA Certified
Hazardous Rating(s)	• Class I, Division 2 • Class II Division 1 & 2 • Class III, Division 1 & 2
Industry Standard(s)	UL 514B

Logistics

Carton Quantity	25
Minimum Pack Quantity	25
Pallet Quantity	7350

Product Assets

[Catalogs - RACO / TayMac / Bell Full Catalog](#)
[Catalogs - Commercial Fittings](#)
[Certifications - UL COC-E195975-4](#)
[Product Logo - LT COND](#)
[Sales Drawings - 35633 Customer Drawing](#)
[SDS - HCC SDS](#)
[Specifications - 35633](#)
[Terms and Conditions - HCC Terms & Conditions](#)



A Hubbell brand