



## 1-1/2 in. 45 Degree Liquidtight Connector, Insulated

By Raco  
Catalog # 3566

1-1/2 in. 45 Degree Liquidtight Connector, Insulated



\*Representative Image

### Features

- Use with flexible metallic liquidtight conduit and Type B flexible nonmetallic liquidtight conduit
- Zinc-electroplated for added corrosion protection
- Insulated
- Innovative split gland-ring assures a perfect seal, preventing pullouts
- Available in trade sizes 3/8 in. through 4 in.
- Sealing washer and heavy-duty locknut included
- All components are reusable

### General

Conduit Type	Liquidtight
EU RoHS Indicator	Contact Manufacturer
Environmental Conditions	Wet Location
Fitting Type	Connectors
Insulation Type	Insulated
Material	Steel/Malleable Iron
UPC	050169035665

### Dimensions

Dimensions	2.813 in x 2.813 in x 4.25 in
Height	4.25 in
Length	2.813 in
Trade Size	1-1/2 in
Weight	1.235 lb
Width	2.813 in

### Certifications And Compliance

Certified Listed	<ul style="list-style-type: none"><li>• UL Listed</li><li>• CSA Certified</li></ul>
Hazardous Rating(s)	<ul style="list-style-type: none"><li>• Class I, Division 2</li><li>• Class II Division 1 &amp; 2</li><li>• Class III, Division 1 &amp; 2</li></ul>
Industry Standard(s)	UL 514B

### Logistics

Carton Quantity	5
Minimum Pack Quantity	5
Pallet Quantity	1000

### Product Assets

<a href="#">Catalogs - RACO / TayMac / Bell Full Catalog</a>
<a href="#">Product Logo - LT COND</a>
<a href="#">Sales Drawings - 3566</a>
<a href="#">SDS - HCC_SDS</a>
<a href="#">Terms and Conditions - HCC Terms &amp; Conditions</a>
<a href="#">Video - RACO: Liquidtight Connectors vs. popular competitor</a>



A proud member of the Hubbell Family.

©2024 Hubbell Incorporated. All rights reserved.  
RACO-3566-SPEC-EN | REV 6/2024