



2 in. 45 Degree Liquidtight Connector, Insulated with Ground Lug

By Raco

Catalog # [3568-3](#)

2 in. 45 Degree Liquidtight Connector, Insulated with Ground Lug



*Representative Image

Features

- Malleable iron construction of the body and nut
- All metallic components are zinc electroplated for added corrosion protection
- Malleable iron castings mate with other components perfectly without strain or distortion
- Patented split gland-ring assures a perfect seal, preventing pullouts
- UL Listed, CSA
- Available in trade sizes 3/8 in. through 2 in.
- Sealing washer and heavy-duty locknut included
- All components are reusable

General

Catalog Number	3568-3
Conduit Type	Liquidtight
Connector Type	Grounding
EU RoHS Indicator	Yes
Environmental Conditions	Wet Location
Fitting Type	Connectors
Insulation Type	Insulated
Material	Steel/Malleable Iron
UPC	050169356838

Dimensions

Dimensions	4.125 in x 3.03 in x 4.125 in
Height	4.125 in

Length	4.125 in
Trade Size	2 in
Weight	3.089 lb
Width	3.03 in

Certifications And Compliance

Buy America(n) Qualified	Contact Manufacturer
Certified Listed	<ul style="list-style-type: none">• UL Listed• CSA Certified• Class I, Division 2• Class II Division 1 & 2• Class III, Division 1 & 2
Hazardous Rating(s)	
Industry Standard(s)	UL 514B

Logistics

Carton Quantity	5
Minimum Pack Quantity	5
Pallet Quantity	750

Product Assets

Catalogs - RACO / TayMac / Bell Full Catalog
Catalogs - Commercial Fittings
Certifications - UL COC-E195975-4
Product Logo - LT COND
Sales Drawings - 35683 Customer Drawing
SDS - HCC SDS
Specifications - 35683
Terms and Conditions - HCC Terms & Conditions



A Hubbell brand